

Main Parameters of HT1000T skid steer loader

Overall specifications			Engine		
Operating Weight	kg	3800	Model	Xinchai 498T / Mitsubishi S4S	
Bucket Capacity	M3	0.5	Rated Power	Kw/rpm	55/2500
Rated Load	kg	1000	Type	4 cylinders, Liquid cooled Diesel	
Max Speed	Km/h	12	Displacement	L	3.168
Track Model	mm	320×84	Emission standard	Euro 3 / EPA 3	
Fuel Tank Capacity	L	80	Working Range		
Hydraulic Standard Flow	L/Min	75	Overall Operating Height	mm	3480
High Flow (Option)	L/Min	140	Max Dumping Height	mm	2230
Overall dimensions			Dumping Reach	mm	715
Transport Dimensions	L*W*H	3500×1782×2150	Dumping Angle at max height	°	40
Min Ground Clearance	mm	200	Rollback of Bucket on ground	°	30
Length with bucket	mm	3500	Rollback of bucket at max height	°	104
Length without bucket	mm	2750	Front Turning Radius	mm	2010
Length of Undercarriage	mm	1700	Rear Turing Radius	mm	1714
Width of Track	mm	320	Rear axle to bumper	mm	1085
Length of Track	mm	1300			

Standard Configuration:

- 1,Germany Rexroth brand hydraulic Pump
- 2,Italy Bondioli Pavesi brand valve
- 3,America Eaton brand motor
- 4,Hydraulic Joystick Control system**
- 5,Luxury Closed Cabin
- 6,Hydraulic Automatic Leveling System
- 7,Double accelerograph control
- 8,Bobcat type quick coupler

